

WENSHING®

# 8dBi Tube Antenna

(902~928MHz)

---

902~928MHz 8dbi Tube Antenna

---

*Model: WS-ANT860SMA-T8*



## Version History

Version	Date	Changes
V1.00	13. Apr, 2018	1 <sup>st</sup> . Edition

## Content

<b>Important Event</b> .....	3
Declaration .....	3
Warranty.....	3
Un-warranty Scope Description.....	3
Contact Us.....	3
<b>Product</b> .....	4
<b>Product Specifications</b> .....	4
<b>View</b> .....	5
<b>Application</b> .....	4
<b>CE Caution Note (European Union)</b> .....	11
<b>FCC Consistent Declaration (U.S.A. Only)</b> .....	11

## Important Event

- This product is in general use for the equipment on the premise of the development, design, manufacture. Do not use that require high security purposes, such as machinery or medical, aviation equipment, machinery and transport-related deaths are directly or indirectly related to the system.
- This product should be in this brochure by the instructions of the types and rated voltage power under the current proper use. If violation of this statement by the safety records of the supply operation, I am afraid our company cannot afford any of the responsibility.
- Do not self-decomposition, alteration, repair of the products also will cause fire, electric shock, fault, and dangerous. In addition, their decomposition, alteration, and repair the product, failure is not within the scope of warranty.
- The products are not waterproof, so please do not use and touch water. Take off and on also please note. Rain, spray, drinks, steam, sweat may be a failure.
- Use of this product, please be sure to use according to the statement recorded by the use of methods to operate. Please do not violate particular attention to the matter reminded to use.
- Please respect this statement recorded by the note. When consumers in contravention of this statement recorded note of the operation, I am afraid our company could not shoulder any responsibility.
- Products are defective, the Company will be responsible for free to amend the flaws, or to the same flawless product or its equivalent products in exchange. However, the Company does not assume based on the requirements of the flaw and loss responsibility.
- The Company reserves the right to retain without notice to users of the cases, the product of hardware / software (version upgrade) is with the right to edit.

### **Declaration**

This product provides different frequency for user selection to meet different telecommunication regulation and FCC/CE on different countries.

### **Warranty**

The warranty time is within one year from purchased date. The warranty scope are used in normal situation and none vandalism. (Some function harmful out of warranty scope and Vandalism are Un-warranty).

### **Un-warranty Scope Description**

- Because the natural disaster, accident or human factor to cause the bad damage.
- Violate the product instruction manual to cause the damage of the products.
- The improper assemble causes damage.
- The products used the unsanctioned accessory to cause damaged.
- Overstep the allowed used environment to cause the products damaged.

### **Contact Us**

WENSHING ELECTRONICS CO., LTD.

No.82, Chong De St. 11054 Shin Yi District, Taipei, Taiwan

Tel: +886-2-27353055

Fax: +886-2-27328813

## Product

This Tube antenna is available in a wide array of types including high sensitivity, alterability, mobility...etc. The Tube antenna has been good at designed, superior performance, and better than cord antenna. The signal and coverage are also broader.

## Product Specifications

Electrical Specifications	
Frequency Range(MHz)	902~928
Gain(dBi)	8
Beam Width(°)	Hor:100 Ver:40
VSWR(°)	≤1.5
Front-to-back ratio(dB)	≥8
Impedance(Ω)	50
Polarization( ° )	Linear polarization
MAX.Power(W)	50
Lightning protection	DC grounding
Specifications	
Connector	SMA-Female
Connector position	Bottom out 15CM
Dimension(mm)	530*100*24
Antenna weight(kg)	----
Wind loading area(m <sup>2</sup> )	≤0.2
Rated wind velocity(m/s)	36.9
Reflector material	aluminum
Radome material	----
Radome color	Black
Operating temperature(°C)	-40~55
Mounting hardware(mm)	----

View

